

# TTS – 7

## Tablet TV system



### Available models:

|                |                                                       |
|----------------|-------------------------------------------------------|
| TTS-7          | 4*DVB-S/S2 to IP stream                               |
| TTS-7CI        | 4*DVB-S/S2 to IP stream with CI                       |
| TTS-7 Wi-Fi    | 4*DVB-S/S2 to IP stream with Wi-Fi                    |
| TTS-7CI Wi-Fi  | 4*DVB-S/S2 to IP stream with CI and Wi-Fi             |
| TTS-7X         | 2*DVB-T/C + 2*DVB-S/S2 to IP stream                   |
| TTS-7XCI       | 2*DVB-T/C + 2*DVB-S/S2 to IP stream with CI           |
| TTS-7X Wi-Fi   | 2*DVB-T/C + 2*DVB-S/S2 to IP stream with Wi-Fi        |
| TTS-7XCI Wi-Fi | 2*DVB-T/C + 2*DVB-S/S2 to IP stream with CI and Wi-Fi |

### Features

- ❑ Digital TV programs with Smart TV
- ❑ SD and HD
- ❑ 4 transponders as unicast or up to 8 programs as multicast

### Technical specification

#### DVB-T/C demodulator

- ❑ Input frequency range 177,5 - 858 MHz
- ❑ Input level 45 ... 80 dBuV
- ❑ Automatic FEC decoder

#### 8PSK/QPSK demodulator

- ❑ Input frequency range 950-2150 Mhz
- ❑ Max. 40 Msymb/s per transponder
- ❑ Input level -65 ... -25 dBm
- ❑ DVB-S/S2 compatible

#### IP output

- ❑ SPTS
- ❑ Max bit rate 40 Mbit/s
- ❑ Multicast and Unicast UDP streaming
- ❑ UpnP-DNLA 1.5 Server
- ❑ IGMP Server
- ❑ Support SAP (Service Announcement Protocol)

### General

- ❑ Power supply 5VDC/x,xA
- ❑ Input connectors 3\* F-female
- ❑ Output connector 1\* RJ-45
- ❑ Dimensions 63 mm\*183 mm\*165 mm

